

S



Charge with speed and simplicity.

amina S is the EV charger made for your car and designed for your home.

Charge up to 22 kW and experience simple charging combined with future-proof smart home integrations.

amina S

Power in Simplicity

amina S is the small and fast EV charger made for your car and designed for your home. Designed and manufactured in Norway, optimised for all weather conditions and tight spaces. The 6-meter fixed cable is convenient, flexible and included at no extra cost.

Charge the way you want

amina S is made for both simple charging and future-proof smart home integrations.

- Plug in and charge – it's as simple as that.
- Smart homes – integrate the charger into a smart home for full smart charging functionality.
- Smart charging apps and electricity providers – connect a supported EV to charge smart and save money.

Maximum power

amina S is built to give your car maximum power when you need it. With a charging speed of up to 22 kW, amina S can add 100 kilometers of range in just one hour.

Technical specifications



General	Dimensions: 264mm x 112mm x 89mm Operating temperature: -30°C to +40°C
Weight	1,0 kg w/o cable 2,4 kg w/ 6m 3-phase 20A cable 3,4 kg w/ 6m 3-phase 32A cable
Power grid and voltages	TN, IT and TT 230V/400V AC 3-phase w/ Neutral 230V AC 1-phase
Charging Cable	Fixed cable included (replaceable) Type 2 plug (EN 62196) AST 100/20: 6m 3-phase 20A AST 100/32: 6m 3-phase 32A
Charging power 20A variant	3-phase output: 3,7 – 13,8 kW 1-phase output: 1,4 – 4,6 kW
Charging power 32A variant	3-phase output: 3,7 – 22,0 kW 1-phase output: 1,4 – 7,4 kW
Energy-meter	1 or 3-phase ±3 % accuracy
Communications interface	Bluetooth LE, and Zigbee Frequency band: 2400 – 2483,5 MHz Maximum output power: 10mW
Degree of protection	Resistant to impact, dust, and water IP54: indoor and outdoor use IK08: impact protection UV-resistant
Electrical protection	Protection class I Overvoltage category III (4 kV)
Integrated RCD	RDC-DD (6mA DC)
Installation	Circuit breaker (max 40A) RCD (max 30mA AC) 4 – 16mm cable diameter Single core or stranded wires 1,5 – 6mm ² w/ ferrules 1,5 – 10mm ² w/o ferrules
Regulations and standards	RED 2014/53/EU EN IEC 62311:2020 EN IEC 61851-1:2019 EN 62196-1:2014 EN 62196-2:2012+A11:2013+A12:2014 IEC 62955:2018 EN IEC 61851-21-2:2021 EN 301 489-1 v2.2.3 EN 301 489-17 v3.2.4 EN 300 328 v2.2.2 RoHS 2011/65/EU EN IEC 63000:2018



aminacharging.com